




FEATURES

-
-
-
-
-
-
-

°C

APPLICATION


-
-



Part No	L@100KHz /0.1V	Tolerance	I _{SAT} Typ.	I _R		R _{DC} Max.
				20°C rise	40°C rise	

Saturation Current will cause L to drop approximately 30%
Temperature Rise Current that causes the specified temperature rise from 25°C ambient.

Soldering Reflow:



Preheat condition: 150 ~200 °C / 60~120 sec.

Allowed time above 217 °C : 60~90 sec.


Max temperature: 260 °C .

Max time at max temperature: 10 sec.

Allowed Reflow time: 2x max.


Packaging Information:

Tape Dimension :



Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
MDTA4030	4.5±0.1	4.5±0.1	1.5±0.1	4.0±0.1	8.0±0.1	12.0±0.3	3.3±0.1	1.75±0.1	0.35±0.05

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.1 to 1.3 N

Product Marking:


Marking	Printing (Inductance)
---------	-----------------------

Reel Dimension: [mm]


The storage period is within71. months after the completion



2.2±0.5



Packaging Quantity:



2000 Pcs/Reel

3 Reel /Inner box(6000 Pcs)

3 Inner box/Carton box(18K Pcs)

Cautions and Warnings:

Storage Conditions:

Operation Instructions: